



CATAS
RP 179206

BAS56



CATAS
RP 179206

BAS57



BAS63

IT Scocca in poliuretano rigido ad alta densità.
Struttura in tubo d'acciaio cromato.

EN High density rigid polyurethane shell.
Chromed steel frame.

ES Asiento en poliuretano rígido de alta densidad. Estructura en tubo cromado.

DE Schale aus festem Polyurethan durchgefärbt.
Verchromtes Stahlrohr.

FR Polyuréthane rigide teinte dans la masse.
Structure en acier chromé.

IT Scocca in poliuretano rigido ad alta densità.
Struttura in tubo d'acciaio verniciato nero.

EN High density rigid polyurethane shell. Frame
base in painted steel black.

ES Asiento en poliuretano rígido de alta densidad. Estructura en tubo pintado negro.

DE Schale aus festem Polyurethan durchgefärbt.
Stahlrohr schwarz beschichtet.

FR Polyuréthane rigide teinte dans la masse.
Structure en acier laqué noir.

IT Scocca in poliuretano rigido ad alta densità.
Struttura in tondino d'acciaio cromato.


EN High density rigid polyurethane shell.
Chromed frame rod steel.

ES Asiento en poliuretano rígido de alta densidad. Estructura en varilla cromada.

DE Schale aus festem Polyurethan durchgefärbt.
Verchromtes Kufengestell.

FR Polyuréthane rigide teinte dans la masse.
Structure chromée en fil d'acier.

Pu (r)
shell
colours



10



0,23



24,7

| BAS56 | 83 | 46 | 51 | 50 | / | 4 | 42 | 40 | 40 | 4,4 | 10 | 0,28 | 25,0 |
|-------|----|----|----|----|---|---|----|----|----|-----|----|------|------|
| BAS57 | 83 | 46 | 51 | 50 | / | 4 | 42 | 40 | 40 | 4,4 | 10 | 0,28 | 25,0 |
| BAS63 | 82 | 45 | 55 | 55 | / | 4 | 42 | 40 | 40 | 6,4 | 10 | 0,28 | 38,7 |